

PRASOL CHEMICALS LIMITED

PRODUCT DATA SHEET

ADDITIV HP 0301



PRASOL®

Type	: Antiwear Hydraulic Additive Package	Product Code : 113
Specifications		Spec. No : PR/ADD HP0301/22/03-00
Appearance	: Brown liquid	CAS No. : not applicable
Density @15°C (g/ml)	: 1.05	(multicomponent)
Viscosity @ 40°C (cSt)	: 176.00	
Viscosity @ 100°C (cSt)	: 13.0	
Flash Point, open cup (°C)	: 105.00	
Nitrogen content (%)	: 1.00	
Zinc content (%)	: 5.00	
Phosphorus content (%)	: 4.00	
Sulphur content (%)	: 8.50	
Packing	: 200 kg in New M.S.Drums, can be engineered upon customer request	
Safety and Handling	: Refer Safety Data Sheet	
Applications	: Additiv HP 0301 is suitable for blending anti-wear hydraulic oils It provides superior wear protection and oxidation stability It is used in premium performance hydraulic fluids.	
Treat Rate	: 0.45% w/w in suitable base oils	
Performance	: DIN 51524 of Part II , III and III* FZG fail load 10th stage, DIN 51354 Part II ISO 11158 HH type hydraulic oil (ASTM D6158-97) Germany iron and steel industry SEB 181222, HLP hydraulic oil Conestoga Pump test ISO 20763/Eaton vickers 1-286-S Bosch Rexroth RE90220 IS 10522	
Technical Service	: For technical assistance, pricing and further information, please contact us through E-mail at - inquiry@prasolchem.com ; sales@prasolchem.com	

Head Office : PRASOL HOUSE, Plot No. A-17/2/3, T. T. C. Indl. Area, Khairne M. I. D. C., Navi Mumbai - 400 710.

Maharashtra, INDIA Tel : +91-22- 69450600/ 61952500 Fax : +91-22- 61952577

Website: www.prasolchem.com

Date of issue : 01.01.2026

Disclaimer

Information herein is given in good faith. Prasol Chemicals Limited makes no representations or warranties as to the completeness or accuracy thereof. Information is supplied upon the condition that the persons receiving the same will make their own determination as to its suitability for their purpose prior to use. Prasol Chemicals Limited shall not be responsible for damages of any nature whatsoever resulting from the use or reliance upon this information. The data provided are based on samples tested and are not guaranteed for all samples or applications. Such data are intended as guides only. No representations or warranties for a particular purpose or any other nature are made with respect to this information or the product.